



Certificate No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

## TYPE CERTIFICATE

### Wind Turbines

This certificate is issued to

Siemens Gamesa Renewable Energy Innovation & Technology SL  
Avda. Ciudad de la Innovación 9-11  
31621 Sarriguren (Navarra)  
Spain

for the wind turbines

SG 3.4-132 MY20 3.465 - 3.65MW

wind turbine class (class, standard, year)

IIA / S, IEC 61400-1/A1, 2010

This certificate attests compliance with IEC 61400 Series as specified in subsequent pages . It is based on the following reference documents:

Design basis evaluation conformity statement  
Dated (\*covered in the design evaluation conformity statement)

IECRE.WE.CS.20.0033-R0  
28.02.2020

Design evaluation conformity statement  
Dated

IECRE.WE.CS.20.0033-R0  
28.02.2020

Type test conformity statement  
Dated

STC-TT-200105-R0  
28.02.2020

Manufacturing conformity statement  
Dated

STC-ME-200104-R0  
28.02.2020

Final evaluation report  
Dated

R13029181-12-R0  
28.02.2020

The conformity evaluation was carried out in accordance with the rules and procedures of the IECRE System  
[www.iecre.org](http://www.iecre.org)

The wind turbine type specification begins on page 2 of this certificate.

Changes in the system design or the manufacturer's quality system are to be approved by the Certification Body. Without approval, the certificate loses its validity.

This certificate is valid until:  
27.02.2025

Approved for issue on behalf of the IECRE  
Certification Body:

UL Renewables



Jörn Gerlach  
Vice Head of Certification Body  
Cuxhaven 28.02.2020

DEWI-OCC GmbH  
Am Seedeich 9  
27472 Cuxhaven, Germany



Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

## TYPE CERTIFICATE

### Wind Turbine

#### Machine parameters:

Power regulation:	Variable speed and pitch control
Rotor orientation:	upwind
Number of rotor blades:	3
Rotor tilt:	6°
Cone angle:	-4°
Rated power:	3.465 MW / 3.65 MW
Rated wind speed $V_r$ :	10.3 m/s (3.465 MW) 10.8 m/s (3.55 MW) 11.2 m/s (3.65 MW)
Rotor diameter:	132 m
Hub height(s):	84 m / 114 m
Hub height operating wind speed range $V_{in} - V_{out}$ :	3 m/s - 25 m/s
Design life time:	20 years
Software version:	Control Architecture V3 or superior

#### Wind conditions:

Characteristic turbulence intensity $I_{ref}$ at $V_{hub} = 15$ m/s:	16.0% (3.465MW) 15.3% (3.55MW) 14.7% (3.65MW)
Annual average wind speed at hub height $V_{ave}$ :	8.5 m/s (3.465 MW) 8.2 m/s (3.55 MW) 7.8 m/s (3.65 MW)
Reference wind speed $V_{ref}$ :	42.5 m/s (3.465 MW) 41.0 m/s (3.55 MW) 39.0 m/s (3.65 MW)
Mean flow inclination:	8 degrees
Hub height 50-year extreme wind speed $V_{e50}$ :	59.5 m/s (3.465 MW) 57.4 m/s (3.55 MW) 54.6 m/s (3.65 MW)



Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

## TYPE CERTIFICATE

### Wind Turbines

#### Electrical network conditions:

Normal supply voltage and range:	690 V $\pm$ 10%
Normal supply frequency and range:	50Hz $\pm$ 6% / 60Hz $\pm$ 6%
Voltage imbalance:	2% - 4%
Maximum duration of electrical power network outages:	not dimensioning
Number of electrical network outages	52/yr.

#### Other environmental conditions (where taken into account):

Design conditions in case of offshore WT :	NA
Normal and extreme temperature ranges:	Normal: -10°C to +40°C Extreme: -20°C to +50°C
Relative humidity of the air:	Up to 95%
Air density:	1.225 kg/m <sup>3</sup> (3.465 MW) 1.200 kg/m <sup>3</sup> (3.55 MW) 1.184 kg/m <sup>3</sup> (3.65 MW)
Solar radiation:	1000 W/m <sup>2</sup>
Lightning protection system (standard and protection class):	IEC 61400-24:2010, LPL I
Earthquake model and parameters (standard and key parameters e.g. spectrum, model, seismic zone, soil class, etc.):	NA
Other design conditions :	NA



Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

**TYPE CERTIFICATE**  
**Wind Turbines**

**Major components:**

\*\*If not otherwise stated, the certificate holder is the manufacturer.

**Blade:**

Manufacturer:	SGRE TPI Shanghai Aeolon
Type:	SG132 TB V2
Material:	Glass fiber reinforced epoxy resin
Blade length:	64.5 m
Number of blades:	3

**Blade bearing:**

Type:	Four point contact double row
Manufacturer:	Laulagun
Drawing / Data sheet / Part No.:	F3113M00DST0125PZD Rev3

**Pitch System:**

Motor / Actuator Type:	Double acting hydraulic cylinder
Pitch Controller Type:	Hydraulic
Manufacturer:	SGRE

**Main shaft:**

Type:	Steel shaft
Manufacturer (Designer):	SGRE
Material:	Forged steel
Drawing / Data sheet / Part No.:	GP482922

**Main bearing:**

Type:	Spherical roller bearing
Manufacturer:	Koyo
Drawing / Data sheet / Part No.:	241/530RHAW33TS



Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

## TYPE CERTIFICATE

### Wind Turbines

#### **Main bearing:**

Type: Spherical roller bearing  
Manufacturer: Timken  
Drawing / Data sheet / Part No.: 230/800YMDWEW886C  
WE-1478-A

#### **Main bearing:**

Type: Spherical roller bearing  
Manufacturer: ZKL  
Drawing / Data sheet / Part No.: 230\_800EW33MH\_TPF\_11517-15\_NV  
231\_630EW33MH\_TPF\_11519-15\_NV

#### **Gearbox:**

Type: Three stages (two planetary gear stages  
plus one helical gear stage)  
Gear Ratio: 1:106.76 (50 Hz)  
1:127.54 (60 Hz)  
Manufacturer: Winergy / Flender Gmbh  
Drawing / Data sheet / Part No.: A5E45222159A

#### **Yaw System:**

*Drive Type:* Sliding bearing, activated by yaw drives  
Manufacturer: SGRE  
Drawing / Data sheet / Part No.: GD268640

*Bearing Type:* Slide bearing provided by axial and radial  
PETP bearing pads  
Manufacturer: SGRE  
Drawing / Data sheet / Part No.: GD268640

*Gear Type:* Geared by yaw drives  
Manufacturer: Bonfiglioli  
Drawing / Data sheet / Part No.: 710T4



Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

## **TYPE CERTIFICATE**

### **Wind Turbines**

*Gear Type:* Geared by yaw drives  
*Manufacturer:* Comer  
*Drawing / Data sheet / Part No.:* PG 2504DSP

*Gear Type:* Geared by yaw drives  
*Manufacturer:* NGC  
*Drawing / Data sheet / Part No.:* FDX204S

*Brake Type:* Integrated in yaw bearing claws with active  
and passive brakes  
*Manufacturer:* SGRE  
*Drawing / Data sheet / Part No.:* GD268640

#### **Generator:**

*Type:* Asynchronous doubly-fed machine  
*Manufacturer (Designer):* SGRE  
*Drawing / Data sheet / Part No.:* CR33-6P  
*Rated Power:* 3615 kW  
*Rated Frequency:* 50 / 60 Hz  
*Rated Speed:* 1120 / 1344 rpm  
*Rated Voltage:* 690 V  
*Rated Current (stator / rotor):* 3000 A / 1198 A  
*Insulation Class:* F / F  
*Degree of Protection:* IP54 / IP23



Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

## TYPE CERTIFICATE

### Wind Turbines

#### Generator:

Type: Asynchronous doubly-fed machine  
Manufacturer: Siemens  
Drawing / Data sheet / Part No.: JFWA-630MR-06A - A5E53000301  
Rated Power: 3585 kW  
Rated Frequency: 50 / 60 Hz  
Rated Speed: 1120 / 1344 rpm  
Rated Voltage: 690 V  
Rated Current (stator / rotor): 2829 A / 1125 A  
Insulation Class: F  
Degree of Protection: IP54 / IP23

#### Converter:

Type: 4 Quadrant DFIG Converter  
Manufacturer (Designer): SGRE  
Drawing / Data sheet / Part No.: DAC 3.3 MW  
DAC CONVERTER 3,4MW PREMIUM  
DAC CONVERTER 3,465MW FIRE  
FIGHTING  
Rated Voltage (grid side): 0 - 690 / 690 ( $\pm 10\%$ ) V  
Rated Current (grid side): 1250 / 660 A  
Degree of Protection: IP54

#### Transformer:

Type: Three phase dry type  
Manufacturer: ABB  
Drawing / Data sheet / Part No.: DTE 3900/36  
Rated Voltage: 33.6 / 0.69 kV  
34.5 / 0.69 kV  
33 / 0.69 kV  
30 / 0.69 kV  
Rated Power: 3900 KVA  
Location (e.g. tower bottom): Nacelle



Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

## TYPE CERTIFICATE

### Wind Turbines

#### Transformer:

Type: Three phase dry type  
Manufacturer: ABB  
Drawing / Data sheet / Part No.: DTE 3900/24  
Rated Voltage: 20 / 0.69 kV  
Rated Power: 3900 KVA  
Location (e.g. tower bottom): Nacelle

#### Transformer:

Type: Three phase dry type  
Manufacturer: SGB  
Drawing / Data sheet / Part No.: DTTH1NG 2500/20  
Rated Voltage: 20 / 0.69 kV  
Rated Power: 3900 / 2900 KVA  
Location (e.g. tower bottom): Nacelle

#### Transformer:

Type: Three phase dry type  
Manufacturer: SGB  
Drawing / Data sheet / Part No.: DTTH1NCG 2500/30  
Rated Voltage: 34.5 / 0.69 kV  
Rated Power: 3900 / 2900 KVA  
Location (e.g. tower bottom): Nacelle

#### Transformer:

Type: Three phase dry type  
Manufacturer: ABB  
Drawing / Data sheet / Part No.: DTE 3900/AF  
Rated Voltage: 34.5 / 0.69 kV  
Rated Power: 3900 KVA  
Location (e.g. tower bottom): Nacelle





Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

## TYPE CERTIFICATE

### Wind Turbines

#### Transformer:

Type: Three phase dry type  
Manufacturer: Hainan Jinpan Smart Technology Co., Ltd.  
Drawing / Data sheet / Part No.: SCLB10-3900/35, 3900 kVA, 35 kV, 50Hz  
Rated Voltage: 35 / 0.69 kV  
Rated Power: 3900 KVA  
Location (e.g. tower bottom): Nacelle

#### Tower:

Manufacturer: Windar renovables  
CS Wind  
Ates Celik  
Gesbey  
Broadwind

Type: Tubular steel tower  
Sections: 5  
Length: 114  
Drawing / Data sheet / Part No.: GD275737

Type: Tubular steel tower  
Sections: 3  
Length: 84  
Drawing / Data sheet / Part No.: GD431557

#### Foundation:

Type: N/A  
Manufacturer: N/A  
Drawing / Data sheet / Part No: N/A

#### Foundation Adaptor:

Type: N/A  
Manufacturer: N/A  
Drawing / Data sheet / Part No.: N/A



Certificate. No.

**IECRE.WE.TC.20.0079-R0**

IECRE - IEC System for Certification  
to Standards Relating to Equipment  
for Use in Renewable Energy  
Applications

**TYPE CERTIFICATE**

**Wind Turbines**

**Manuals:**

Operation & maintenance manual: See R13029181-2-R0

Transport manual: See R13029181-2-R0

Installation & commissioning. manual: See R13029181-2-R0